



US009637071B2

(12) **United States Patent**
Marks et al.

(10) **Patent No.:** **US 9,637,071 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **MOLDABLE NATURAL FIBER NONWOVEN WIRE HARNESS TROUGH AND METHOD OF CONSTRUCTION THEREOF**

(71) Applicant: **Federal-Mogul Powertrain, Inc.**,
Southfield, MI (US)

(72) Inventors: **Philip E. Marks**, Chester Springs, PA (US); **Eric K. Staudt**, Reading, PA (US); **Ritesh Mehbubani**, Exton, PA (US); **Ali Khosroshahi**, Exton, PA (US)

(73) Assignee: **Federal-Mogul Powertrain LLC**,
Southfield, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/859,632**

(22) Filed: **Sep. 21, 2015**

(65) **Prior Publication Data**
US 2016/0082904 A1 Mar. 24, 2016

Related U.S. Application Data

(60) Provisional application No. 62/052,798, filed on Sep. 19, 2014.

(51) **Int. Cl.**
H02G 3/04 (2006.01)
B60R 16/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B60R 16/0215** (2013.01); **B29C 43/003** (2013.01); **B29C 43/021** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC Y10T 428/24198; H02G 3/0437; H02G 3/045; H02G 3/04
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,864,082 A 9/1989 Ono et al.
5,832,960 A 11/1998 Amatsutsu et al.
(Continued)

FOREIGN PATENT DOCUMENTS

DE 20300098 U1 3/2003

OTHER PUBLICATIONS

International Search Report, mailed Dec. 22, 2015 (PCT/US2015/051152).

(Continued)

Primary Examiner — Alexander Thomas

(74) *Attorney, Agent, or Firm* — Robert L. Stearns;
Dickinson Wright, PLLC

(57) **ABSTRACT**

A nonwoven trough and method of construction thereof are provided. The nonwoven trough includes at least one nonwoven wall formed from a mixture of bonded natural cellulosic fibers and thermoplastic fibers. The at least one nonwoven wall extends along a longitudinal axis and has a midsection and opposite end portions. The midsection has a base and a pair of walls extending upwardly from the base to provide the midsection with a generally U-shaped cross-section taken generally transversely to the longitudinal axis. At least one flange extends laterally from the at least one nonwoven wall, wherein the flange is configured for attachment to a vehicle member.

16 Claims, 8 Drawing Sheets

